



4-270DST DST Hinge 60x60 Pr01 180°



Avantages

- Hinge with DIRAL-SNAP-Technology.
- For nested doors.
- Hinge visible.
- RH / LH application.
- 180° Opening angle.
- Installation tool-less or tool-less / screw-on.

Materials

- **Hinge halves:** zinc die, black
- **Pin:** stainless steel
- **Pin molded in:** steel, zinc plated
- **Snap wedges:** sintered metal, coated



Hinge

	Part Number	Version	Clamping range (S)	Pin version	Installation type	Delivery Unit
a)	418-9202.00-00015	clip-in	1.2 - 1.7 mm	pressed in	tool-less	10 pcs.
a)	418-9202.00-00020	clip-in	1.7 - 2.2 mm	pressed in	tool-less	10 pcs.
a)	418-9202.00-00025	clip-in	2.2 - 2.7 mm	pressed in	tool-less	10 pcs.
a)	418-9202.00-00030	clip-in	2.7 - 3.2 mm	pressed in	tool-less	10 pcs.
a)	418-9202.00-00035	clip-in	3.2 - 3.7 mm	pressed in	tool-less	10 pcs.
b)	418-9203.00-00015	Screws M8 molded in	1.2 - 1.7 mm	pressed in	tool-less / screw-on	10 pcs.
b)	418-9203.00-00020	Screws M8 molded in	1.7 - 2.2 mm	pressed in	tool-less / screw-on	10 pcs.
b)	418-9203.00-00025	Screws M8 molded in	2.2 - 2.7 mm	pressed in	tool-less / screw-on	10 pcs.
b)	418-9203.00-00030	Screws M8 molded in	2.7 - 3.2 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9208.00-00015	with countersunk holes for M8	1.2 - 1.7 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9208.00-00020	with countersunk holes for M8	1.7 - 2.2 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9208.00-00025	with countersunk holes for M8	2.2 - 2.7 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9208.00-00030	with countersunk holes for M8	2.7 - 3.2 mm	pressed in	tool-less / screw-on	10 pcs.
c)	418-9208.00-00035	with countersunk holes for M8	3.2 - 3.7 mm	pressed in	tool-less / screw-on	10 pcs.

292-0301.15-00000 **Tool for uninstallation**

292-0306.80-02530 **Tool for uninstallation**

292-0701.15-01530 **Reinforcement plate for cutout**

